

Tuinhuis (Garden house) Color



1. PRODUCT DESCRIPTION

Opaque water-based stain. For garden houses and other garden wood.

The matt, opaque colours were specially developed to complement the natural colours in the garden.

filling without detracting from the natural beauty of the wood.

Leaves the wood structure visible. Xyladecor Garden Shed Color brings atmosphere and colour into the garden.

Protects against weather influences.

Scope

Specially developed for the protection and decoration of garden wood. Suitable for gazebos, arbors, fences, pergolas, garden furniture, flower boxes, wooden toys, etc. Suitable for rough, planed surfaces, new or weathered wood. Also for wood that was previously treated with carbolineum.

Properties

Protects against weather influences. Delays ageing. Water repellent.

Very soft, breathable and does not flake off.

Leaves the wood structure visible. Harmless to plants and animals. Covering in two layers.

Aspect

Mat.

Colors



Landelijk wit



Olijfboom



Houtskool



Wilde tijm



Lindegroen



Witte Jasmijn



Nevelgrijs



Berkengrijs



Mistral grijs



Zachte klei

Packaging

2. SUBSTRATE / SYSTEMS

The wood must be clean and dry. Fill all cracks and holes with Polyfilla product.

New wood

Degrease and dust off.

To protect new wood against insects and wood rot first Xyladecor Garden Wood Protector or Use Xyladecor Combi BP. Apply 2 coats of Xyladecor Garden Shed Color.

Already treated wood

First remove or sand down previous coats of paint or stain (after degreasing).

If necessary, first clean rough wood with a hard brush and soapy water. Afterwards thoroughly let it dry. Further treat as new wood.

Tropical wood species

When applied to some types of wood (cedar, afzelia, merbau, etc.), projections of wood colouring agents occur. Test in advance on a small surface.

3. PROCESSING OF THE PRODUCT

Mix the contents of the package well.

Apply evenly with a brush (synthetic fibres) or a paint gun.

Ready to use.

Clean tools with warm water immediately after use.

Return

Planed wood: 20 to 25 m²/l per coat.

Rough, unsanded wood: 6 to 10 m²/l per coat.

Drying time

At 20°C and 60% R.H:

Drying time: 1h.

Can be repainted: apply the second layer after 2 hours but within 48 hours of the previous layer.

Light sanding between coats.

4. SAFETY AND CONSERVATION

Safety

Avoid contact with eyes and skin. Keep out of reach of children.

Do not throw waste into the sink.

VOC content

This product contains maximum 130 g/l VOC.

EU limit value for this product (category A/e): 130 g/l (2010).

Storage

Close container tightly after use. Store in a cool and frost-free place.

This technical data sheet, as of February 28, 2017, cancels and replaces all previous issues. This technical data is based on our own knowledge and testing and is provided to you by way of guidance. However, this does not imply any formal liability for the use of our products. Please always check with our services whether there is a new data sheet of recent date.

For further advice call +32 (0)800.32.000.

In case of intoxication, immediately contact
the Poison Control Centre at +32 (0)70.245.245.

Akzo Nobel Paints Belgium nv/sa, PB 80, B-1800 Vilvoorde, Tel. +32 (0)2.254.22.11